



by Honeywell

---

**Technical Specifications**

## Self-Retracting Lifeline FALCON


**Description:**

The self-retracting lifeline Falcon range is the safest, most robust range of composite retractable lifelines on the market. Tested and approved for horizontal applications (when used with locking karabiner and a 1m steel anchorage sling 1002897).

References	Description
<b>1011728</b>	Falcon 6,20 m galvanized wire
<b>1011729</b>	Falcon 6,20 m stainless steel cable
<b>1011742</b>	Falcon 10 m galvanized wire
<b>1011743</b>	Falcon 10 m stainless steel cable
<b>1011746</b>	Falcon 15 m galvanized wire
<b>1011747</b>	Falcon 15 m stainless steel cable
<b>1011750</b>	Falcon 20 m galvanized wire
<b>1011751</b>	Falcon 20 m stainless steel cable



The cable is now supplied with double ferrule





by Honeywell

## Features & benefits :

References	Description		weight	Dimensions
<b>1011728</b>	Falcon 6,20 m galvanized wire	Ø 4,5 mm	4,1 kg	255 x 213 x 101 mm
<b>1011729</b>	Falcon 6,20 m stainless steel cable	Ø 4,5 mm	4,1 kg	255 x 213 x 101 mm
<b>1011742</b>	Falcon 10 m galvanized wire	Ø 4,5 mm	5,0 kg	255 x 213 x 101 mm
<b>1011743</b>	Falcon 10 m stainless steel cable	Ø 4,5 mm	5,0 kg	255 x 213 x 101 mm
<b>1011746</b>	Falcon 15 m galvanized wire	Ø 4,5 mm	6.7 kg	342 x 246 x 101 mm
<b>1011747</b>	Falcon 15 m stainless steel cable	Ø 4,5 mm	6.7 kg	342 x 246 x 101 mm
<b>1011750</b>	Falcon 20 m galvanized wire	Ø 4,5 mm	7.7 kg	342 x 246 x 101 mm
<b>1011751</b>	Falcon 20 m stainless steel cable	Ø 4,5 mm	7.7 kg	342 x 246 x 101 mm

- \* Highly visible load indicator at the snap hook
- \* High quality, corrosion resistance components
- \* Quick-activating braking mechanism stops the fall
- \* No annual factory re-certification required\*\*
- \* Dual swivels (unit top and snap hook)
- \* Lightweight, robust composite unit (torsion relieved)

Housing : high-impact Nylon

Hub : Heat Treated Aluminium

Breaking Mechanism : Stainless Steel and Bronze

Cable lifeline : Ø 4.5 mm in Galvanized or Stainless Steel

Snap hook : Zinc-Plated Steel, Double-Locking Swivel Snap Hook with 22mm gate opening

Temperature: -30°C to +50°C

Breaking Strength : 12 KN

**EN 360**

\*\*The CE standard requires inspection by a trained end-user competent person, following the Miller Repair Guide.

**LAW of 19 MARCH 93**

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail [techniserv.hsp@honeywell.com](mailto:techniserv.hsp@honeywell.com)

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : [www.honeywellsafety.com](http://www.honeywellsafety.com)