

TURBOLITE

Description





2 m. Self retracting webbing lifeline. The first affordable alternative to shock-absorbing lanyards used in fall factor 2. Adapted to all situations when working with low space clearance. Can be used on both ways around.

References :

- 1018015 Twistlock karabiner x 2
- 1018013 Twistlock karabiner + Scaff Hook
- 1018014 Scaff Hook + Twistlock karabiner
- 1017900 Twistlock karabiner + Snap Hook

Features

- Housing :** Impact resistant nylon
- Braking System:** stainless steel
- Webbing:** Vectran (25.4mm x 1.5mm)
Length : 2 m
- Shock Absorber :** Length 62cm
- Max. rated Load :** 136 kg (use in up anchorage point)
100 kg (use in down level)

Ref	1018015	1018013	1018014	1017900
Length	2 m	2 m	2 m	2 m
Anchorage connection	Twistlock karabiner opening 18mm	Twistlock karabiner opening 18mm	Scaff Hook Opening 65mm	Twistlock karabiner opening 18mm
				
Harness connection	Twistlock karabiner opening 18mm	Scaff Hook Opening 65mm	Twistlock karabiner opening 18mm	Snap Hook Opening 21mm
Poids	0,877 kg	1,252 kg	1,252 kg	0.860 kg

Standard

EN 360-ANSI A10.32 and Z359-2007-OSHA-CSA

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv@sperian.com

